

JOB _____ ITEM # _____ QTY # _____

MODEL NUMBER:

- | | | |
|---------------------------------|------------------------------------|------------------------------------|
| <input type="checkbox"/> SK24GR | <input type="checkbox"/> CL12GR-DB | <input type="checkbox"/> CL24GR-DB |
| <input type="checkbox"/> CL24GR | <input type="checkbox"/> CL18GR-DB | <input type="checkbox"/> SK24GR-DB |

DIMENSIONS:

- SK24GR - 36"H x 24"D X 21 1/4"L
- CL24GR - 36"H x 24"D X 24"L
- CL12GR-DB - 36"H x 12"D X 24"L
- CL18GR-DB - 36"H x 18"D X 24"L
- CL24GR-DB - 36"H x 24"D X 24"L
- SK24GR-DB - 36"H x 24"D X 21 1/4"L



CL24GR

STANDARD FEATURES

- 304 Stainless Steel, Welded and Polished Top Assembly, Ends, Back and Bottom
- Standard with Glass Rack Slides to Hold (3) Glass Racks
- Removable Perforated Top, Designated by "-DB" Otherwise Smooth Top
- Die-Cast Heavy Duty 6" Stainless Steel Equipment Legs with Adjustable Feet
- Custom Lengths Available
- Optional: Two (2) Adjustable Shelves
- Constructed to Meet NSF Specifications

Model #	# of Wells	A	CM Watts	CM Amps	HF Watts	Amps 120V	Amps 208V	Amps 240V	NEMA Cap Number		
									120V	208V	240V
SK24GR	Smooth Top	21 1/4"									
CL24GR	Smooth Top	24"									
CL12GR-DB	With Perforated Pan	24"									
CL18GR-DB	With Perforated Pan	24"									
CL24GR-DB	With Perforated Pan	24"									
SK24GR-DB	With Perforated Pan	21 1/4"									

Part #	Description	Part #	Description
--------	-------------	--------	-------------

SPEC U-13