

JOB _____ ITEM # _____ QTY # _____

MODEL NUMBERS:

- ☐ ACSCA-ST-1020
- ☐ ACSCA-ST-1420
- ☐ ACSCA-ST-2020


Model #	Rack Size	A	B	C
ACSCA-ST-1020	10" x 20"	22.375"	30.375"	41.5"
ACSCA-ST-1420	14" x 20"	22.375"	34.375"	41.5"
ACSCA-ST-2020	20" x 20"	22.375"	40.375"	41.5"

Options

COMMON OPTIONS

<input type="checkbox"/>	B	Corner Bumper (adds 2" to overall length and width)
<input type="checkbox"/>	PB	Perimeter Bumper (adds 2" to overall length and width)
<input type="checkbox"/>	WB	Two locking casters
<input type="checkbox"/>	Y4	Polyurethane 4
<input type="checkbox"/>	Y5	Polyurethane 5

Dish guides add 4" to height.
Shipping weight-200 lbs



ACSCA-ST-2020-AT3

CAPACITY

- Up to 175 cups (in racks) and
- approx. 100 to 144 saucers.

SPECIFICATIONS

Model ACSCA-ST mobile cup and saucer dispenser.

FRAME AND BODY:

The frame is constructed of all welded heavy gauge stainless steel. The body is stainless steel on all sides and top, and is fitted with a stainless steel tubular push handle. The front panel is removable for adjustment access.

CUP DISPENSING MECHANISM:

The rack carrier, constructed of all welded 16 ga. stainless steel, is raised by a series of coil springs attached to the frame. Ball bearing guides and a single stainless steel aircraft type cable keep the carrier level in all directions, even with an unbalanced load. The cable runs over pre-lubricated plated steel pulleys. Adjustment for varying weights is easily accomplished by removing the front panel, then engaging or disengaging individual springs as required.

SAUCER DISPENSERS:

The unit includes two Model AT adjustable, drop-in saucer dispensers (see Page D-9 for specifications). The saucer dispenser size (AT1, AT2 or AT3) is required when ordering.

CASTERS:

The unit is mounted on four 4" diameter, heavy duty, swivel, casters.