

JOB _____ ITEM # _____ QTY # _____



1ATG, 1ATGH



2ATG, 2ATGH

SPECIFICATIONS

Models ATG unheated and ATGH heated tubular frame, mobile dish dispensers.

FRAME: The frame is constructed of 1" O.D. 16 ga. stainless steel tubing.

SHELVES: Each shelf is press formed from a single sheet of 18 ga. stainless steel. It is flanged down 1-5/16" on all four sides and formed back at a 30° angle for rigidity. Each inside corner is fitted with an ABS black plastic bracket and sleeve to accommodate an upright. The bottom shelf on all models is set 8" above the floor.

DISPENSERS: ATG models are fitted with model AT adjustable, drop-in dish dispensers. ATGH models are fitted with model ATH heated, adjustable, drop-in dish dispensers (See page D-9 for specifications of these dispensers). On heated units, the dispensers plug into a central junction box which is fitted with a 4' long, 3 wire cord set with NEMA 5-15P plug for 120 volt or NEMA 6-15P for 220 volt.* These units are also available for oval platters, Model ATDO.

CASTERS: Units are mounted on four, 4" diameter heavy duty, swivel casters with non-marking rubber tires.

MODEL NUMBERS:

- 1ATG1 2ATG7 3ATGH4
- 1ATG2 2ATG75 3ATGH5
- 1ATG3 2ATG8 3ATGH6
- 1ATG4 2ATGH1 3ATGH7
- 1ATG5 2ATGH2 3ATGH75
- 1ATG6 2ATGH3 3ATGH8
- 1ATG7 2ATGH4 4ATG1
- 1ATG75 2ATGH5 4ATG2
- 1ATG8 2ATGH6 4ATG3
- 1ATGH1 2ATGH7 4ATG4
- 1ATGH2 2ATGH75 4ATG5
- 1ATGH3 2ATGH8 4ATG6
- 1ATGH4 3ATG1 4ATG7
- 1ATGH5 3ATG2 4ATG75
- 1ATGH6 3ATG3 4ATG8
- 1ATGH7 3ATG4 4ATGH1
- 1ATGH75 3ATG5 4ATGH2
- 1ATGH8 3ATG6 4ATGH3
- 2ATG1 3ATG7 4ATGH4
- 2ATG2 3ATG75 4ATGH5
- 2ATG3 3ATG8 4ATGH6
- 2ATG4 3ATGH1 4ATGH7
- 2ATG5 3ATGH2 4ATGH75
- 2ATG6 3ATGH3 4ATGH8

Model #	Dish Sizes	A	B	C
1ATG1	5.125" Max.	14"	14"	36"
1ATG2	5.25" to 5.875" Max.	14"	14"	36"
1ATG3	6" to 6.625" Max.	17"	17"	36"
1ATG4	6.75" to 7.375" Max.	17"	17"	36"
1ATG5	7.5" to 8.25" Max.	17"	17"	36"
1ATG6	8.375" to 9.25" Max.	19"	19"	36"
1ATG7	9.375" to 10.25" Max.	19"	19"	36"
1ATG75	10.375" to 11.25" Max.	19"	19"	36"
1ATG8	11.375" to 12" Max.	21"	21"	36"
1ATGH1	5.125" Max.	14"	14"	36"
1ATGH2	5.25" to 5.875" Max.	14"	14"	36"
1ATGH3	6" to 6.625" Max.	17"	17"	36"
1ATGH4	6.75" to 7.375" Max.	17"	17"	36"
1ATGH5	7.5" to 8.25" Max.	17"	17"	36"
1ATGH6	8.375" to 9.25" Max.	19"	19"	36"
1ATGH7	9.375" to 10.25" Max.	19"	19"	36"
1ATGH75	10.375" to 11.25" Max.	19"	19"	36"
1ATGH8	11.375" to 12" Max.	21"	21"	36"
2ATG1	5.125" Max.	24"	14"	36"
2ATG2	5.25" to 5.875" Max.	24"	14"	36"
2ATG3	6" to 6.625" Max.	30"	17"	36"
2ATG4	6.75" to 7.375" Max.	30"	17"	36"
2ATG5	7.5" to 8.25" Max.	30"	17"	36"

SPEC E-18

Model #	Capacity	A	B	C
2ATG6	8.375" to 9.25" Max.	34"	19"	36"
2ATG7	9.375" to 10.25" Max.	34"	19"	36"
2ATG75	10.375" to 11.25" Max.	34"	19"	36"
2ATG8	11.375" to 12 Max.	38"	21"	36"
2ATGH1	5.125" Max.	24"	14"	36"
2ATGH2	5.25" to 5.875" Max.	24"	14"	36"
2ATGH3	6" to 6.625" Max.	30"	17"	36"
2ATGH4	6.75" to 7.375" Max.	30"	17"	36"
2ATGH5	7.5" to 8.25" Max.	30"	17"	36"
2ATGH6	8.375" to 9.25" Max.	34"	19"	36"
2ATGH7	9.375" to 10.25" Max.	34"	19"	36"
2ATGH75	10.375" to 11.25" Max.	34"	19"	36"
2ATGH8	11.375" to 12 Max.	38"	21"	36"
3ATG1	5.125" Max.	31"	19"	36"
3ATG2	5.25" to 5.875" Max.	31"	19"	36"
3ATG3	6" to 6.625" Max.	39"	23"	36"
3ATG4	6.75" to 7.375" Max.	39"	23"	36"
3ATG5	7.5" to 8.25" Max.	39"	23"	36"
3ATG6	8.375" to 9.25" Max.	44"	26"	36"
3ATG7	9.375" to 10.25" Max.	44"	26"	36"
3ATG75	10.375" to 11.25" Max.	44"	26"	36"
3ATG8	11.375" to 12 Max.	48"	29"	36"
3ATGH1	5.125" Max.	31"	19"	36"
3ATGH2	5.25" to 5.875" Max.	31"	19"	36"
3ATGH3	6" to 6.625" Max.	39"	23"	36"
3ATGH4	6.75" to 7.375" Max.	39"	23"	36"
3ATGH5	7.5" to 8.25" Max.	39"	23"	36"
3ATGH6	8.375" to 9.25" Max.	44"	26"	36"
3ATGH7	9.375" to 10.25" Max.	44"	26"	36"
3ATGH75	10.375" to 11.25" Max.	44"	26"	36"
3ATGH8	11.375" to 12 Max.	48"	29"	36"
4ATG1	5.125" Max.	24"	24"	36"
4ATG2	5.25" to 5.875" Max.	24"	24"	36"
4ATG3	6" to 6.625" Max.	30"	30"	36"
4ATG4	6.75" to 7.375" Max.	30"	30"	36"
4ATG5	7.5" to 8.25" Max.	30"	30"	36"
4ATG6	8.375" to 9.25" Max.	34"	34"	36"
4ATG7	9.375" to 10.25" Max.	34"	34"	36"
4ATG75	10.375" to 11.25" Max.	34"	34"	36"
4ATG8	11.375" to 12 Max.	38"	38"	36"
4ATGH1	5.125" Max.	24"	24"	36"

Model #	Capacity	A	B	C
4ATGH2	5.25" to 5.875" Max.	24"	24"	36"
4ATGH3	6" to 6.625" Max.	30"	30"	36"
4ATGH4	6.75" to 7.375" Max.	30"	30"	36"
4ATGH5	7.5" to 8.25" Max.	30"	30"	36"
4ATGH6	8.375" to 9.25" Max.	34"	34"	36"
4ATGH7	9.375" to 10.25" Max.	34"	34"	36"
4ATGH75	10.375" to 11.25" Max.	34"	34"	36"
4ATGH8	11.375" to 12 Max.	38"	38"	36"

Options

COMMON OPTIONS

<input type="checkbox"/>	R	Rotating Bumper (Adds 5
<input type="checkbox"/>	SSTC	Stainless Steel Tube Covers Per tublet
<input type="checkbox"/>	WB	Two locking casters
<input type="checkbox"/>	Y4	Polyurethane 4
<input type="checkbox"/>	Y5	Polyurethane 5