



ACS-STH-2020.jpg

HEIGHT 36"- Other heights available.
Dish guides add 4" to height.
Add 2" to length and width for wraparound bumpers. Shipping weight-150

HEIGHT 36"- Other heights available.
Dish guides add 4" to height. Add 2" to length and width for wrap-around bumpers. Shipping weight-200

Voltage Single PH.	Total Wattage	Amps
120	1600	12.5
208	1600	7.2

Model #	Tray Size	Length	Width	Height
ACS-ST-1020	10" X 20"	27.9375"	26.625"	36"
ACS-ST-1420	14" X 20"	32"	28"	36"
ACS-ST-2020	20" X 20"	37.4375"	27.125"	36"
ACS-STH-1020	10" X 20"	27.9375"	26.625"	36"
ACS-STH-1420	14" X 20"	32"	28"	36"
ACS-STH-2020	20" X 20"	37.4375"	27.125"	36"

JOB _____ ITEM # _____ QTY # _____



MODEL ACS-STH CAPACITY
Up to 175 cups, approx. 100 to 144 saucers.

MODEL NUMBERS:

- ☐ ACS-ST-1020
- ☐ ACS-ST-1420
- ☐ ACS-ST-2020
- ☐ ACS-STH-1020
- ☐ ACS-STH-1420
- ☐ ACS-STH-2020

SPECIFICATIONS

CABINET: The body and top are of unibody design, constructed of heavy gauge stainless steel panels formed to provide rigidity. Heated models (ACS-STH) are insulated on sides and top.

CUP DISPENSER: The unit is fitted with a model ADIF adjustable drop-in cup dispenser (see catalog page D-13 for specifications).

SAUCER DISPENSERS: The unit includes two Model AT adjustable, drop-in saucer dispensers. (See page D-9 for specifications.) Saucer dia. required when ordering. Max. 6-5/8"

HEATING SYSTEM: The model ACS-STH heating system consists of heating elements of 1500 watt total capacity, thermostatically regulated and wired for 120 or 208 volt (as specified) single phase power supply. A recessed control panel is complete with on-off switch, neon pilot light, adjustable thermostat and a receptacle for a cord set. A 4' long three wire cord set fitted with NEMA 5-15P plug for 120 volt or NEMA 6-15P plug for 208 volt is provided.

CASTERS: Unit is mounted on four 4" diameter heavy duty, double ball bearing, swivel casters with non-marking rubber tires.

COMMON OPTIONS

- ☐ **B** Corner Bumper (adds 2" to overall length and width)
- ☐ **PB** Full Perimeter Bumper (adds 2" to overall length and width)
- ☐ **V** Vertical Bumpers (adds 1
- ☐ **WB** Two locking casters
- ☐ **Y4** Polyurethane 4
- ☐ **Y5** Polyurethane 5