



RIA69-1826-20

Series RIA, aluminium angle guide, open roll-in racks to accommodate 18" x 26" sheet pans, for use in refrigerators and freezers.

FRAME

The vertical uprights and the top and bottom cross bracing are 2" x 1" x 1/8" thick extruded aluminum channels welded to form a rigid frame. Caster support channels are 1-7/8" x 4" x 1/8" thick extruded aluminum, fully welded to the vertical uprights and bottom cross supports.

GUIDES

The guides are 1" x 1-1/2" x .100 thick extruded aluminum angles welded to the vertical uprights, with all corners chamfered and deburred.

TIE ROD

All models have 1/2" diameter aluminum tie rods welded to the front and rear vertical uprights for extra rigidity.

CASTERS

The units are mounted on four 5" diameter, heavy duty, swivel casters.

JOB _____ ITEM # _____ QTY # _____

MODEL NUMBER:

- ☐ RIA64-1826-11 ☐ RIA58-1826-16 ☐ RIA69-1826-20
☐ RIA69-1826-12 ☐ RIA64-1826-18

DIMENSIONS:

- RIA64-1826-11 - 64.5"H x 20.5"W X 26"D
- RIA69-1826-12 - 69.5"H x 20.5"W X 26"D
- RIA58-1826-16 - 58.5"H x 20.5"W X 26"D
- RIA64-1826-18 - 64.5"H x 20.5"W X 26"D
- RIA69-1826-20 - 69.5"H x 20.5"W X 26"D

Capacity: Last digits of model number indicate the quantity of 18" x 26" pans per rack.

NOTE: Before ordering Roll-In rack, be sure to verify the clear opening provided in the refrigerator or freezer being used with the Roll-In rack.

COMMON OPTIONS

<input type="checkbox"/>	5x2	Heavy-duty Casters (set of 4)(requires SB option)
<input type="checkbox"/>	B	Corner Bumper (adds 2" to overall length and width) Requires SB
<input type="checkbox"/>	EMB	Personalized Embossment (12 letters per line - price per line) Per Line
<input type="checkbox"/>	FL	Floor Lock (requires SB option)
<input type="checkbox"/>	PB	Full Perimeter Bumper (adds 2" to overall length and width)
<input type="checkbox"/>	PH	Push Handle
<input type="checkbox"/>	PS	Pan Stop
<input type="checkbox"/>	SB	Solid Bottom
<input type="checkbox"/>	V	Vertical Bumpers (adds 1
<input type="checkbox"/>	WB	Two locking casters
<input type="checkbox"/>	Y5	Polyurethane 5

Model #	Description	Height Inches	Width Inches	Depth Inches	Channel Ht. Inches	Pan Capacity	No Of Steam Table Pans	Ship Wt. (lbs)
RIA64-1826-11	Angle Guide	64.5"	20.5"	26"	5"		11	65
RIA69-1826-12	Angle Guide	69.5"	20.5"	26"	5"		12	70
RIA58-1826-16	Angle Guide	58.5"	20.5"	26"	3"		16	67
RIA64-1826-18	Angle Guide	64.5"	20.5"	26"	3"		18	75
RIA69-1826-20	Angle Guide	69.5"	20.5"	26"	3"		20	84

SPEC I-7

PIPER

The Food-Focused Equipment Company

300 S. 84th Avenue | Wausau, WI 54401
Phone: 800-544-3057 | Fax: 715-842-3125
www.piperonline.net

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times. We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.