



JOB _____ ITEM # _____ QTY # _____

MODEL NUMBER:

☐ Anliker L

DIMENSIONS:

- 21.26"H x 12.40"W X D

Unit Comparisons

	GSM 4	GSM 5 Star	XL, XL Star, & MultiCut-240
HP	1/2	1/2	1
RPMs	340	340	280
Upper Housing	Cast Aluminum	Stainless Steel	Cast Aluminum
Blades Available	47	52	42,44,42
Antimicrobial Protection Pusher		X	X
Antimicrobial Protection Blades	X	X	

Cord and Plug

Attached six-foot flexible 3-wire cord and plug fits a grounded receptacle.

Construction

The housing, removable hinged hopper head, food hoppers, removable food pusher and ejector plate are made of polished cast aluminum.

There are 47 cutting discs available. The discs are antimicrobial durable composite fiberglass. The knives are hardened, ground, leathered and hand-polished to a razor sharp edge for precision cutting and long life.

Design

Ergonomic 45° incline for convenient feeding, cutting and ejection of food. Separate food hopper permits continuous cutting of long products. The food pusher enables even pressure to be applied when cutting food. The hopper head, food pusher and cutting discs are easily removable, without the use of tools, for quick cleaning.

Warranty

Two years parts and labor.

SHIPPING INFORMATION

- Shipping Weight: 43.65
- Shipping Cubic Feet:
- Freight Class: 100

Standard Features

- Kidney shaped material pusher is made from mold cast food grade aluminum
- Powerful 1/2 HP gear-driven motor
- Optimum plate speed of 336 RPMs
- Polished food grade cast aluminum construction & sealed upper housing
- Double safety interlock - hopper head and food pusher
- Ergonomic 45° food hopper incline
- Removable hopper head and food pusher (no tools required)
- Discs are antimicrobial durable composite fiberglass & dishwasher safe
- Stainless steel knives are hardened, ground, leathered and hand-polished
- 47 discs are available

Capacity

Processes up to 600 lbs. per hour. Ideal for up to 300-400 meals.

Motor

1/2 HP, 115V-60HZ-1 Phase, 3 amps, automatic reset thermal overload protection.

On/Off Latch (interlocks)

The hopper latch serves as the on/off switch and interlock for the hopper head. The unit will not operate with the hopper head open or unlatched.

Gear Drive

Sealed planetary gear transmission with permanent grease lubrication. Output 336 RPMs.



F1



G3



0



23



HS



S2

Cutting Discs


Model	Description	inches	mm
SU7-5	Slicing Disc 9/32" (7mm) Wavy Cut	9/32	7
0-5	Shredding Disc 23/64" (9mm)	23/64	9
00-5	Shredding Disc 7/16" (11mm)	7/16	11
1-5	Shredding Disc 9/32" (7mm)	9/32	7
11-5	Shredding Disc 5/64" (2mm)	5/64	2
14-5	Grating Disc, Fine Powder	fine cut (parmesan and romano cheese powder)	
23-5	Specialty Shredding Disc 3/32"	3/32	2.5
3-5	Shredding Disc 3/16" (5mm)	3/16	5
4-5	Shredding Disc 5/32" (4mm)	5/32	4
7-5	Shredding Disc 1/8" (3mm)	1/8	3
9-5	Shredding Disc 3/32" (2.5mm)	3/32	2.5
BT10-5	French Fry Disc 3/8" (10mm)	3/8	10
BT6-5	French Fry Disc 15/64" (6mm)	15/64	6
BT7-5	French Fry Disc 9/32" (7mm)	9/32	7
BT8-5	French Fry Disc 5/16" (8mm)	5/16	8
F1-5	Slicing Disc 1/32" (1mm)	1/32	1
F2-5	Slicing Disc 5/64" (2mm)	5/64	2
G10-5	Slicing Disc 3/8" (10mm)	3/8	10
G12-5	Slicing Disc 15/32" (12mm)	15/32	12
G3-5	Slicing Disc 1/8" (3mm)	1/8	3
G4-5	Slicing Disc 5/32" (4mm)	5/32	4



PA4




BT7



W6



SM



SCV-1

SCH-3

WR-3

Cutting Discs

Model	Description	inches	mm
PA4K-5	Julienne Disc 5/32" (4mm)	5/32	4
PA5K-7	Julienne Disc 3/16" X 5/32"	3/16 x 5/32	5 x 4
S1.5-5	Julienne Disc 1/16" (1.5mm)	1/16	1.5
S2-5	Julienne Disc 5/64" (2mm) SQUARE	5/64	2
S3-5	Julienne Disc 1/8" X 5/64" (3mm)	1/8 x 5/64	3 x 2
SM1.5-5	Sickle Disc 1/16" (1.5mm)	1/16	1.5
SM2.5-5	Sickle Disc 3/32" (2.5mm)	3/32	2.5
SM3.5-5	Sickle Disc 9/94" (3.5mm)	9/94	3.5
SM4.5-5	Sickle Disc 11/64" (4.5mm)	11/64	4.5
SM5.5-5	Sickle Disc 7/32" (5.5mm)	7/32	5.5
SM6.5-5	Sickle Disc 1/4" (6.5mm)	1/4	6.5
SU5-5	Slicing Disc 3/16" (5mm)	3/16	5
SU5-7	Slicing Disc 3/16" (5mm)	3/16	5
TO-5	Slicing Disc 3/16" (5mm)	3/16	5
W10-5	Dicing Disc 3/8"	3/8	10
W14-5	Dicing Disc 9/16"	9/16	14
W20-5	Dicing Disc Soft Products Only 25/64" x 25/64" x 25/64"	25/64 x 25/64 x 25/64	20 x 20 x 20
W6-5	Dicing Disc 1/4" x 1/4" x 5/16"	1/4 x 1/4 x 5/16	6 x 6 x 8
W8-5	Dicing Disc 5/16"	5/16	8

Accessories

Model	Description
-------	-------------

SPEC T-1

G6-5	Slicing Disc 15/64" (6mm)	15/64	6
G8-5	Slicing Disc 5/16" (8mm)	5/16	8
HS-5	Shaving Disc 1/64" (.5mm)	1/64	.5

SCH-3	Horizontal disc storage case (3 discs)
SCH-4	Horizontal disc storage case (4 discs)
SCV-1	Vertical disc storage case (1 disc) *Will not hold cubing or dicing discs
SCV-7/3	Vertical disc storage rack (3 discs)
WR3	Three peg wall rack storage

SPEC T-1